



## MATERIAL SAFETY DATA SHEET

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

**Product Name:** Original Sculpey®, Sculpey III®, Super Sculpey®, Super Sculpey® Firm, Sculpey® MOLDBAKER™ & POLYMER CLAY CONDITIONER, Granitex™, Premo! Sculpey®, Sculpey SuperFlex BAKE & BEND®, Amazing! Eraser Clay®, Sculpey® UltraLight™, Sculpey® Keepsake Clay, Sculpey® Bake Shop™, Sculpey® Pluffy™

**Product Use:** Oven hardening modeling material for hobby use

**Manufacturer:**  
Polyform Products Company  
1901 Estes Avenue  
Elk Grove Village, IL 60007 USA  
Phone: 1-847-427-0020

**Emergency Telephone Number:**  
1-847-427-0020  
available only during office hours

Date of Preparation: 05-11-2009

### 2. HAZARD IDENTIFICATION

#### Emergency Overview

Do not inhale fumes during baking. Overheating oven hardening polymer clays will result in blackening and release of irritating gases including hydrogen chloride vapor.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Components</u>	<u>CAS number</u>	<u>Weight %</u>
-------------------	-------------------	-----------------

Oven hardening modeling material composed of polyvinyl chloride, plasticizer, fillers and colorants. This material contains no dangerous substances to be declared.

### 4. FIRST AID MEASURES

<b>Eye Contact:</b>	Rinse eye thoroughly with plenty of water. If symptoms persist, seek medical attention.
<b>Skin Contact:</b>	Wash with soap and water.
<b>Ingestion:</b>	Wash out mouth with water. If symptoms persist, seek medical attention.
<b>Inhalation:</b>	Seek fresh air after inhalation of fumes in the case of overheating material in oven.

### 5. FIRE-FIGHTING MEASURES

<b>Flash Point:</b>	n/a
<b>Autoignition Temperature:</b>	n/a
<b>Explosion Limits in Air:</b>	Not explosive
<b>Extinguishing Agents:</b>	Use water spray jet, foam, carbon dioxide, dry chemical.
<b>Hazardous Decomposition Products:</b>	In the case of overheating in oven, carbon monoxide, carbon dioxide and noxious hydrochloric acid vapors.
<b>Special Protective Equipment for Fire Fighters:</b>	Wear self-contained breathing apparatus with full face piece and protective clothing.

Original Sculpey®, Sculpey III®, Super Sculpey®, Super Sculpey® Firm, Sculpey® MOLDBAKER™ & POLYMER CLAY CONDITIONER, Granitex™, Premo! Sculpey®, Sculpey SuperFlex BAKE & BEND®, Amazing! Eraser Clay®, Sculpey® UltraLight™, Sculpey® Keepsake Clay, Sculpey® Bake Shop™, Sculpey® Pluffy™

## 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** None. In case of overheating material, turn off oven. Ventilate area by opening nearest window. Seek fresh air, if fumes are inhaled.

**Environmental Precautions:** Contain spill.

**Methods for Cleaning Up:** Collect and reuse or dispose with domestic refuse.

## 7. HANDLING AND STORAGE

**Handling:** Do not heat above 175°C (350°F), allow to come in contact with an open flame or use with a hot knife or wire. Use oven thermometer when hardening material in oven. Do not use microwave oven for baking. Do not overbake. Do not exceed the recommended baking temperature or time. Wash hands with soap and water after use.

**Storage:** Store unused material in a cool, dry place preferably in a sealed non-reactive container.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Exposure Limits:** No threshold exposure limit values known.

**Eye Protection:** n/a

**Skin and Body Protection:** n/a

**Respiratory Protection:** n/a

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Color:</b>	Various	<b>pH:</b>	n/a
<b>Appearance:</b>	Solid, malleable	<b>Solubility in Water:</b>	Not soluble
<b>Odor:</b>	Characteristic	<b>Reactivity in Water:</b>	Non-reactive
<b>Boiling Point:</b>	n/a	<b>Specific Vapor Density (Air=1):</b>	n/a
<b>Melting Point:</b>	n/a	<b>Vapor Pressure:</b>	n/a

## 10. STABILITY AND REACTIVITY

**Stability:** Product is stable.

**Polymerization:** Not known to occur.

**Hazardous Decomposition Products:** Hydrochloric acid vapors

**Materials to Avoid:** None

**Conditions to Avoid:** None when used as intended.

## 11. TOXICOLOGICAL INFORMATION

**Effects and Symptoms of Acute Exposure:** None expected.

**Effects and Symptoms of Chronic Exposure:** None expected.

### Carcinogen Listing

**NTP:** No      **IARC:** No      **OSHA:** No

## 12. ECOLOGICAL INFORMATION

No harmful effects to the environment are known if material is used as intended and disposed of in the appropriate manner.

### 13. DISPOSAL CONSIDERATIONS

If recycling is not available, dispose with domestic refuse. Observe all federal, state and local regulations.

### 14. TRANSPORT INFORMATION

Not regulated by US DOT.

### 15. REGULATORY INFORMATION

Material is non-hazardous and not to be labeled.  
This product has been reviewed by a toxicologist and carries the AP seal.  
The labeling conforms to ASTM D-4236.

### 16. OTHER INFORMATION

n/a: not applicable

This MSDS applies to the following colors which are associated with hazardous and/or non-hazardous ingredients.

<b><u>Products</u></b>	<b><u>Colors with Hazardous Ingredients</u></b>
Original Sculpey®	None
Sculpey III®	None
Sculpey® MOLDBAKER™ & POLYMER CLAY CONDITIONER	None
Granitex™	None
Premo! Sculpey®	None
Sculpey SuperFlex BAKE & BEND®	None
Amazing! Eraser Clay®	None
Sculpey® UltraLight™	None
Sculpey® Keepsake Clay	None
Sculpey® Bake Shop™	None
Sculpey® Pluffy™	None

The MSDS supersedes a previous MSDS dated: 2/16/2009  
Prepared by: K. Rush 5/11/2009

The information contained herein is provided in good faith and is subject to change without notice. It is believed to be accurate and represents the best information currently available to us. However, we make no warranty, fitness for a particular purpose or of any other type, expressed or implied, with respect to products described or data or information provided. We assume no liability resulting from the use of such products, data or information. Users should determine the suitability of the information for their particular purpose. The user assumes all risk arising from their use of the material. The user is required to comply with all laws and regulations relating to the purchase, use, storage and disposal of the material and must be familiar with and follow generally accepted safe handling procedures.