

**21711-1001**

**SAFETY DATA SHEET**  
**WINSOR & NEWTON ARTISTS' FIXATIVE (AEROSOL)**

**1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING**

PRODUCT NAME WINSOR & NEWTON ARTISTS' FIXATIVE (AEROSOL)  
PRODUCT NO. 3033913  
APPLICATION Fixing pastel, chalk, charcoal and pencil drawings.  
SUPPLIER Colart Fine Art & Graphics Limited  
Whitefriars Avenue  
Harrow  
Middlesex HA3 5RH  
+44 (0) 208 4274343  
44 (0) 208 42433217

**2 COMPOSITION/INFORMATION ON INGREDIENTS**

Name	EC No.	CAS-No.	Content	Classification
ACETONE	200-662-2	67-64-1	30-60%	F;R11 Xi;R36 R66 R67
BUTANE	203-448-7	106-97-8	10-30%	F+;R12
ETHANOL	200-578-6	64-17-5	10-30%	F;R11
METHANOL	200-659-6	67-56-1	< 1%	F;R11 T;R23/24/25,R39/23/24/25

The Full Text for all R-Phrases are Displayed in Section 16

**3 HAZARDS IDENTIFICATION**

Extremely flammable. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. Irritating to eyes.

CLASSIFICATION Xi;R36. F+;R12. R66, R67.

**PHYSICAL AND CHEMICAL HAZARDS**

Aerosol containers can explode when heated, due to excessive pressure build-up. The product is extremely flammable, and explosive vapour/air mixtures may be formed even at normal room temperatures.

**4 FIRST-AID MEASURES****INHALATION**

NOTE! Keep affected person away from heat, sparks and flames! Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

**INGESTION**

Immediately rinse mouth and provide fresh air. DO NOT INDUCE VOMITING! Get medical attention.

**SKIN CONTACT**

Wash the skin immediately with soap and water. Remove contaminated clothing. Get medical attention if irritation persists after washing.

**EYE CONTACT**

Spray in the eyes: Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

**5 FIRE-FIGHTING MEASURES****EXTINGUISHING MEDIA**

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

**SPECIAL FIRE FIGHTING PROCEDURES**

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

**UNUSUAL FIRE & EXPLOSION HAZARDS**

Extremely flammable. Forms explosive mixtures with air. May travel considerable distance to source of ignition and flash back. Aerosol cans may explode in a fire.

**WINSOR & NEWTON ARTISTS' FIXATIVE (AEROSOL)****SPECIFIC HAZARDS**

Aerosol containers can explode when heated, due to excessive pressure build-up.

**6 ACCIDENTAL RELEASE MEASURES****PERSONAL PRECAUTIONS**

Provide adequate ventilation. In case of inadequate ventilation, use respiratory protection. Avoid inhalation of vapours and aerosol spray.

**ENVIRONMENTAL PRECAUTIONS**

Do not discharge into drains, water courses or onto the ground. Contain spillages with sand, earth or any suitable adsorbent material.

**SPILL CLEAN UP METHODS**

Wear necessary protective equipment.

**7 HANDLING AND STORAGE****USAGE PRECAUTIONS**

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

**STORAGE PRECAUTIONS**

Keep away from heat, sparks and open flame. Store in a cool and well-ventilated place. Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Pressurised container: Must not be exposed for temperatures above 50°C.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
ACETONE	OES	500 ppm	1210 mg/m3	1500 ppm	3620 mg/m3
BUTANE	OES	600 ppm	1450 mg/m3	750 ppm	1810 mg/m3
ETHANOL	OES	1000 ppm	1920 mg/m3		
METHANOL	OES	200 ppm(Sk)	266 mg/m3(Sk)	250 ppm(Sk)	333 mg/m3(Sk)

**INGREDIENT COMMENTS**

OES = Occupational Exposure Standard.

**PROTECTIVE EQUIPMENT****ENGINEERING MEASURES**

Provide adequate general and local exhaust ventilation.

**RESPIRATORY EQUIPMENT**

In case of inadequate ventilation use suitable respirator.

**HAND PROTECTION**

Use suitable protective gloves if risk of skin contact.

**EYE PROTECTION**

Use eye protection. Wear approved chemical safety goggles where eye exposure is reasonably probable.

**OTHER PROTECTION**

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

**HYGIENE MEASURES**

**DO NOT SMOKE IN WORK AREA!** Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke. Use appropriate skin cream to prevent drying of skin.

**9 PHYSICAL AND CHEMICAL PROPERTIES****APPEARANCE**

Aerosol

**WINSOR & NEWTON ARTISTS' FIXATIVE (AEROSOL)**

ODOUR	Solvent.		
PHYSICAL DATA COMMENTS	Information given concerns the major ingredient.		
FLASH POINT (°C)	<40.	AUTO IGNITION TEMPERATURE (°C)	400 - 580
FLAMMABILITY LIMIT - LOWER(%)	1.8	FLAMMABILITY LIMIT - UPPER(%)	9.5

**10 STABILITY AND REACTIVITY****STABILITY**

Avoid: Heat, sparks, flames.

**CONDITIONS TO AVOID**

Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.

**HAZARDOUS DECOMPOSITION PRODUCTS**

By fire, toxic gases (CO, CO<sub>2</sub>, NO<sub>x</sub>) may be formed.

**11 TOXICOLOGICAL INFORMATION****INHALATION**

In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system.

**SKIN CONTACT**

Repeated exposure may cause skin dryness or cracking.

**EYE CONTACT**

Irritating to eyes. Spray and vapour in the eyes may cause irritation and smarting. May cause severe irritation to eyes.

**ROUTE OF ENTRY**

Inhalation.

**TARGET ORGANS**

Central nervous system. Respiratory system, lungs.

**MEDICAL SYMPTOMS**

Inhalation may cause: Headache. Dizziness. Stupor.

**12 ECOLOGICAL INFORMATION****ECOTOXICITY**

Not known.

**MOBILITY**

Highly volatile and will rapidly evaporate to the air

**13 DISPOSAL CONSIDERATIONS****GENERAL INFORMATION**

Do not puncture or incinerate even when empty.

**DISPOSAL METHODS**

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

**14 TRANSPORT INFORMATION**

UK ROAD CLASS

2

**WINSOR & NEWTON ARTISTS' FIXATIVE (AEROSOL)**

PROPER SHIPPING NAME	AEROSOLS, FLAMMABLE, NOS (Contains Acetone and Liquefied Petroleum Gases)		
UN NO. ROAD	1950	ADR CLASS NO.	2, 5F
ADR CLASS	Class 2.1: Flammable gases.	HAZARD NO. (ADR)	23 Flammable gas.
ADR LABEL NO.	3	CEPIC TEC(R) NO.	20G53
RID CLASS NO.	2	UN NO. SEA	1950
IMDG CLASS	2.1	IMDG PAGE NO.	2102
IMDG PACK GR.	N/A	EMS	2-13
MFAG	620	MARINE POLLUTANT	No.
UN NO. AIR	1950	AIR CLASS	2.1
AIR SUB CLASS	N/A	AIR PACK GR.	N/A

**15 REGULATORY INFORMATION**

## LABELLING



Irritant



Extremely Flammable

## RISK PHRASES

R12	Extremely flammable.
R36	Irritating to eyes.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

## SAFETY PHRASES

S2	Keep out of the reach of children
S9	Keep container in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S23	Do not breathe vapour/spray.
S25	Avoid contact with eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37	Wear suitable gloves.
S51	Use only in well-ventilated areas.
S56	Dispose of this material and its container to hazardous or special waste collection point.

## EU DIRECTIVES

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. System of specific information relating to Dangerous Preparations. 2001/58/EC.

**16 OTHER INFORMATION**

DATE 2/11/2007

## RISK PHRASES IN FULL

R11	Highly flammable.
R12	Extremely flammable.
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R36	Irritating to eyes.
R39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

**WINSOR & NEWTON ARTISTS' FIXATIVE (AEROSOL)****DISCLAIMER**

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.