

50305 Pg 1

MATERIAL SAFETY DATA SHEET

May be used to comply with OSHA's Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.

HMIS HAZARD RATING

HEALTH	0	0 = INSIGNIFICANT	3 = HIGH
FLAMMABILITY	3	1 = SLIGHT	4 = EXTREME
REACTIVITY	0	2 = MODERATE	

SAFETEC OF AMERICA

TRANSPORTATION INFORMATION

PROPER SHIPPING NAME	Flammable liquid, n.o.s. (Ethanol)		
HAZARD CLASS / PKG. GRP.	3 / III	REF.	173.150(b)(c)
IDENTIFICATION NUMBER	NA1993	LABEL	None Required Ground

SECTION 1 - PRODUCT / COMPANY IDENTIFICATION

IDENTITY (AS USED ON LABEL AND LIST)

Page 1 of 2

p.a.w.s. Personal Antimicrobial Wipe

MANUFACTURER'S NAME

Safetec of America, Inc.

EMERGENCY TELEPHONE NUMBER (24 Hours)

(800) 255-3924

ADDRESS (NUMBER, STREET, P.O. BOX)

887 Kensington Avenue @ William L. Gaiter Pkwy.

TELEPHONE NUMBER FOR INFORMATION

(716) 895-1822

(CITY, STATE AND ZIP CODE)

Buffalo, NY 14215

DATE PREPARED

September 1, 2004

SUPERSEDES

February 11, 2004

SECTION 2 - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

HAZARDOUS COMPONENTS (SPECIFIC CHEMICAL IDENTITY; COMMON NAME(S))	CAS #	% (wt.) (OPTIONAL)	OSHA PEL/STEL		ACGIH TLV/TWA/STEL	
			PPM	MG/M ³	PPM	MG/M ³
Ethyl Alcohol	64-17-5	35 - 45	1000 (PEL)		1000 (TLV)	
Chloroxyleneol	88-04-0	0.44 - 0.56	None Established		None Established	

This product is not known to contain a substance subject to Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR 372 at or above minimal amounts.

SECTION 3 - HEALTH HAZARD DATA

ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EXPOSURE

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Brief (minutes) inhalation will not cause adverse effects, although, constant inhalation may cause irritation to upper respiratory tract.

Remove victim to fresh air; provide oxygen if breathing is difficult; seek medical attention if required.

EYES: Brief contact may cause mild irritation; prolonged contact may cause moderate irritation associated with redness.

Flush eyes with clear running water for a minimum of 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

INGESTION: Small amounts swallowed incidental to normal handling are not likely to cause injury. Swallowing larger amounts may cause injury.

DO NOT induce vomiting; seek immediate medical attention. Vomiting may be induced only under the supervision of a physician.

HEALTH HAZARDS (ACUTE AND CHRONIC): Acute effects are possible irritation and discomfort; no known chronic effects have been established.

CARCINOGENICITY

NTP?

No

IARC MONOGRAPHS?

No

OSHA REGULATED?

No

No additional information

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Preexisting skin, eye, or respiratory disorders may become aggravated through prolonged exposure.

50300 152

MATERIAL SAFETY DATA SHEET

IDENTITY (AS USED ON LABEL AND LIST)

p.a.w.s. Personal Antimicrobial Wipe

Page 2 of 2

Date: September 1, 2004

SECTION 4 - FIRE FIGHTING MEASURES

FLASH POINT (METHOD USED)

97°F (TOC)

FLAMMABLE LIMITS (% Volume in Air for Lowest Flashing Component)

LEL: 3.3

UEL: 19

EXTINGUISHING MEDIA

Dry chemicals, alcohol-type or all-purpose foam, CO₂

SPECIAL FIRE FIGHTING PROCEDURES

Use water spray to cool fire-exposed containers and structures. Use water spray to disperse vapors; re-ignition is possible

UNUSUAL FIRE AND EXPLOSIVE HAZARDS

Flammable material. Toxic gases (such as carbon monoxide and formaldehyde) may be released in a fire. Concentrated vapors may be flammable.

SECTION 5 - PRECAUTIONS FOR SAFE HANDLING AND USE / LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED

Remove all sources of ignition. Small spills may be flushed with large amounts of water; larger spills should be collected for disposal.

WASTE DISPOSAL METHODS

Dispose of in accordance with Local, State, and Federal regulations. Products classified as non-hazardous may become hazardous waste upon contact with other products. Refer to "40 CFR Protection of Environment Parts 260-299" for complete waste disposal regulations. Consult your Local, State, or Federal Environmental Protection Agency before disposing of any chemicals.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep container(s) tightly closed when not in use. Avoid inhalation of high concentration of vapors. Store in cool, dry area away from possible sources of ignition. Keep this and other chemicals out of reach of children.

SECTION 6 - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION

Ordinarily, none required

VENTILATION

LOCAL EXHAUST: Required
MECHANICAL (GENERAL): Yes

PROTECTIVE GLOVES

Ordinarily, none required

EYE PROTECTION

Ordinarily, none required

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Ordinarily, none required

WORK / HYGIENIC PRACTICES

Practice safe work habits. Use according to label instructions.

SECTION 7 - PHYSICAL / CHEMICAL PROPERTIES

BOILING POINT

174.6°F

SPECIFIC GRAVITY (WATER=1)

0.936

VAPOR PRESSURE (mm Hg)

No data

MELTING POINT

Not applicable

VAPOR DENSITY (AIR=1)

1.59 (ALC.)

pH

3.8 - 6.4

SOLUBILITY IN WATER

Slight

EVAPORATION RATE (n-BUTYL ACETATE=1)

1.7 (ALC.)

APPEARANCE AND ODOR

Off-white; mild fresh fragrance

% VOLATILES (BY WEIGHT)

68.75

SECTION 8 - STABILITY AND REACTIVITY

STABILITY

UNSTABLE:

STABLE: XXX

CONDITIONS TO AVOID

Extreme temperatures; sources of ignition

INCOMPATIBILITIES (MATERIALS TO AVOID)

Strong oxidizers; strong acids

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Decomposition will not occur if handled / stored properly. Thermal decomposition may emit typical products of combustion.

HAZARDOUS POLYMERIZATION

MAY OCCUR:

WILL NOT OCCUR: XXX

CONDITIONS TO AVOID

Heat

The information contained herein is believed to be accurate but is not warranted to be so. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed.