# MATERIAL SAFETY DATA SHEET

MAY BE USED TO COMPLY WITH OSHA'S HAZARD COMMUNICATION STANDARD 29CRF 1910.1200



				By St	aples	
DATE PF	REPARED: 07/21/20	010 5	SIGNATUR	E OF PREPARER (OPTIONAL)		
SECTION 1 CHEMICAL PR	RODUCT / NAME					
Product/Chemical Name: Product No: SEB13A CAS Number: M Other Designations: N/	HP 1300 AR ixture	) - Odyssey		Framing		
					echnoiogies	
SECTION 2 COMPOSITIO	N / INFORMATION		INTS		-	
	CAS	EU		OSHA	ACGIH	OTHER
ngredient Name:	NUMBER	NUMBER	%	PEL	TLV	LIMITS
Styrene-Acrylate Copolymer	Proprietary		N/A	Toner is regulated under OSH otherwise regu		e not
				OSHA PEL: 15		
ron Oxide (Black Pigment)	Proprietary		N/A	5mg/m <sup>3</sup> for r	espirable fracti	on
Vax	Proprietary		N/A	ACGIH TWA: 10mg/m <sup>3</sup> for nui	isance particula	ate
Silica	Proprietary		N/A			
	IDENTIFICATION halation					/HMIS
Farget Organs:       N/A         Acute Effects:       N/A					HEALTH FLMMBLTY.	1
	of respiratory tract.				REACTIVITY	
8	e irritation by mechan	ical abrasion.			PPE (Sec.8)	-
Skin: Slight irritation.				1		
ngestion: None known.						
Carcinogenicity: N/A						
•	se congestion.			n of dust in the respiratory syster		
the dust		NUISANCE PART	•	e airborne particles (dust), it is re according to the American Confe		
SECTION 4 FIRST AID ME						
nhalation: Remove to fresh	h air. Treat any irritat	on symptomatica	lly. Call a p	hysician if condition persists.		
Eye Contact: In case of conta 15 minutes. Rer	ct immediately flush move any contact len		•			
Skin Contact: Wash well with	soap and running wa	ter.				
ngestion: N/A						
-	et appropriate in-plan	•	ommunity m	edical support		
	and symptoms perist	-				
lote to Physicians: N/						
Special Precautions / Procedu	ures: N/A					

SECTION 5	FIRE FIGH	TING MEASURES
Flash Point:	N/A	
Flash Point M		
Burning Rate:		
-		: Not Determined
LEL:	N/A	. Not Determined
UEL:	N/A N/A	
		at Clicht (UMIC NEDA)
Flammability		
Extinguishing Unusual Fire		Water spray, dry chemical, foam, carbon dioxide, or halon type extinguishers.
	•	
Hazardous Co	ompustion Pr	Under certain conditions some aliphatic aldehydes and carboxylic acids
Eiro Eighting	Instructions	may form. Do not release runoff from fire controls methods to sewers or waterways.
		Because fire may produce toxic thermal decomposition products, wear a
i ne-i ignung	Equipment.	self-contained breating apparatus (SCBA) with full facepiece operated
		in pressure-demand or positive-pressure mode.
SECTION 6	ACCIDENT	AL RELEASE MEASURES
Spill / Leak Pr		N/A
Small Spills:	Scoop into a	container for disposal, suction up remaining material with a high efficiency
	vacuum clea	aner.
Large Spills:	Scoop into a	container for disposal, suction up remaining material with a high efficiency
	vacuum clea	aner.
Containment:		ills, avoid suspending particles, collect for later disposal. Do not release
	into sewers	or waterways.
Cleanup:		equirements.
Regulatory Re	equirement:	N/A
		AND STORAGE
Handling Pred	cautions:	Keep containers closed at all times. Avoid creating dust. Keep away from ignition sources.
		······································
Storage Requ	irements:	Store in a cool, dry location.
Storage Requ Regulatory Re	irements:	Store in a cool, dry location.
Regulatory Re	irements: equirement:	Store in a cool, dry location.
Regulatory Re	irements: equirement: EXPOSURE	Store in a cool, dry location. N/A
Regulatory Re SECTION 8	irements: equirement: EXPOSURE Controls:	Store in a cool, dry location. N/A
Regulatory Re SECTION 8 Engineering C	irements: equirement: EXPOSURE Controls: Provide gene	Store in a cool, dry location. N/A E CONTROLS / PERSONAL PROTECTION
Regulatory Re SECTION 8 Engineering C	irements: equirement: EXPOSURE Controls: Provide gen below OSHA	Store in a cool, dry location. N/A E CONTROLS / PERSONAL PROTECTION eral or local exhaust ventilation systems to maintain airborne concentrations
Regulatory Re SECTION 8 Engineering C	irements: equirement: EXPOSURE Controls: Provide gen below OSHA dispersion in	Store in a cool, dry location. N/A E CONTROLS / PERSONAL PROTECTION eral or local exhaust ventilation systems to maintain airborne concentrations A PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant
Regulatory Re SECTION 8 Engineering C Venilation:	irements: equirement: EXPOSURE Controls: Provide genubelow OSHA dispersion ir e Controls:	Store in a cool, dry location. N/A E CONTROLS / PERSONAL PROTECTION eral or local exhaust ventilation systems to maintain airborne concentrations A PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant
Regulatory Re SECTION 8 Engineering C Venilation: Administrative	irements: equirement: EXPOSURE Controls: Provide genubelow OSHA dispersion ir e Controls:	Store in a cool, dry location. N/A  CONTROLS / PERSONAL PROTECTION  eral or local exhaust ventilation systems to maintain airborne concentrations A PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant to the work area by controlling it at its source.
Regulatory Re SECTION 8 Engineering C Venilation: Administrative	irements: equirement: EXPOSURE Controls: Provide genubelow OSHA dispersion ir e Controls:	Store in a cool, dry location. N/A  CONTROLS / PERSONAL PROTECTION  eral or local exhaust ventilation systems to maintain airborne concentrations A PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant to the work area by controlling it at its source.  Seek professional advise prior to respirator selection and use.
Regulatory Re SECTION 8 Engineering C Venilation: Administrative	irements: equirement: EXPOSURE Controls: Provide genubelow OSHA dispersion ir e Controls:	Store in a cool, dry location. N/A  CONTROLS / PERSONAL PROTECTION  eral or local exhaust ventilation systems to maintain airborne concentrations A PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant to the work area by controlling it at its source.  Seek professional advise prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear
Regulatory Re SECTION 8 Engineering C Venilation: Administrative	irements: equirement: EXPOSURE Controls: Provide genubelow OSHA dispersion ir e Controls:	Store in a cool, dry location. N/A
Regulatory Re SECTION 8 Engineering C Venilation: Administrative	irements: equirement: EXPOSURE Controls: Provide genubelow OSHA dispersion ir e Controls:	Store in a cool, dry location. N/A
Regulatory Re SECTION 8 Engineering C Venilation: Administrative	irements: equirement: EXPOSURE Controls: Provide genubelow OSHA dispersion ir e Controls:	Store in a cool, dry location. N/A
Regulatory Re SECTION 8 Engineering C Venilation: Administrative	irements: equirement: EXPOSURE Controls: Provide genubelow OSHA dispersion ir e Controls:	Store in a cool, dry location. N/A
Regulatory Re SECTION 8 Engineering C Venilation: Administrative Respiratory P	irements: equirement: EXPOSURE Controls: Provide genu below OSHA dispersion ir e Controls: Protection:	Store in a cool, dry location. N/A  CONTROLS / PERSONAL PROTECTION  eral or local exhaust ventilation systems to maintain airborne concentrations A PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant to the work area by controlling it at its source.  Seek professional advise prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operation (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. Warning! Air-purified respirators do not protect workers in oxygen-deficient
Regulatory Re SECTION 8 Engineering C Venilation: Administrative Respiratory P	irements: equirement: EXPOSURE Controls: Provide genu below OSHA dispersion ir e Controls: Protection:	Store in a cool, dry location. N/A
Regulatory Re SECTION 8 Engineering C Venilation: Administrative Respiratory P	irements: equirement: EXPOSURE Controls: Provide genu below OSHA dispersion ir e Controls: Protection:	Store in a cool, dry location. N/A
Regulatory Re SECTION 8 Engineering C Venilation: Administrative Respiratory P	irements: equirement: EXPOSURE Controls: Provide genu below OSHA dispersion ir e Controls: Protection:	Store in a cool, dry location. N/A
Regulatory Re SECTION 8 Engineering C Venilation: Administrative Respiratory P	irements: equirement: EXPOSURE Controls: Provide genu below OSHA dispersion ir e Controls: Protection:	Store in a cool, dry location. N/A
Regulatory Re SECTION 8 Engineering C Venilation: Administrative Respiratory P	irements: equirement: EXPOSURE Controls: Provide gene below OSHA dispersion ir e Controls: rotection:	Store in a cool, dry location. N/A ECONTROLS / PERSONAL PROTECTION eral or local exhaust ventilation systems to maintain airborne concentrations A PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant the work area by controlling it at its source. Seek professional advise prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operation (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. <i>Warning! Air-purified respirators do not protect workers in oxygen-deficient atmosheres.</i> ment: Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye and face protection regulations (29CFR 1910.133). Contact lenses are not eye protective devices. Appropriate
Regulatory Re SECTION 8 Engineering C Venilation: Administrative Respiratory P	irements: equirement: EXPOSURE Controls: Provide gene below OSHA dispersion ir e Controls: rotection: othing/Equipt	Store in a cool, dry location. N/A
Regulatory Re SECTION 8 Engineering C Venilation: Administrative Respiratory P	irements: equirement: EXPOSURE Controls: Provide gene below OSHA dispersion ir e Controls: rotection: othing/Equipt	Store in a cool, dry location. N/A
Regulatory Re SECTION 8 Engineering C Venilation: Administrative Respiratory P	irements: equirement: EXPOSURE Controls: Provide gene below OSHA dispersion ir e Controls: rotection: othing/Equipt	Store in a cool, dry location. N/A
Regulatory Re SECTION 8 Engineering C Venilation: Administrative Respiratory P	irements: equirement: EXPOSURE Controls: Provide genu- below OSH/ dispersion in e Controls: Protection: Protection: Othing/Equiption hs: Make d Equipment:	Store in a cool, dry location. N/A
Regulatory Re SECTION 8 Engineering C Venilation: Administrative Respiratory P Protective Clo Safety Station Contaminated	irements: equirement: EXPOSURE Controls: Provide genu- below OSH/ dispersion in e Controls: Protection: Protection: othing/Equiption hs: Make d Equipment: Never eat, d	Store in a cool, dry location. N/A <b>ECONTROLS / PERSONAL PROTECTION</b> eral or local exhaust ventilation systems to maintain airborne concentrations A PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant to the work area by controlling it at its source. Seek professional advise prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operation (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. <i>Warning! Air-purified respirators do not protect workers in oxygen-deficient</i> <i>atmosheres</i> . ment: Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye and face protection regulations (29CFR 1910.133). Contact lenses are not eye protective devices. Appropriate protection must be worn instead of, or in conjunction with contact lenses. remergency eyewash stations and washing facilities available in work area. Separate contaminated wprk clothing from street clothes. Launder before re-use. Remove this material from your shoes and clean personal protective equipment.
Regulatory Re SECTION 8 Engineering C Venilation: Administrative Respiratory P Protective Clo Safety Station Contaminated	irements: equirement: EXPOSURE Controls: Provide genu- below OSH/ dispersion in e Controls: Protection: Protection: othing/Equiption hs: Make d Equipment: Never eat, d	Store in a cool, dry location. N/A

# SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Physical State: So	lid	Water Solubility:	Negligible
Appearance and Odor:	Black, free flowing powder, odorless	Other Solubilities:	N/A
Odor Threshold:	N/A	Boiling Point:	N/A
Vapor Pressure:	N/A	Freezing/Melting Point:	N/A
Vapor Density (Air=1):	Heavier than air.	Viscosity:	N/A
Formula Weight:	N/A	Refractive Index:	N/A
Density:	N/A	Surface Tension:	N/A
Specific Gravity:	(H <sub>2</sub> O)=1, at 4°C): 1.5-2.5	% Volatile:	N/A
pH:	N/A	Evaporation Rate:	N/A

# SECTION 10 STABILITY AND REACTIVITY

Stability:StablePolymerization:Will not occurChemical Incompatibilities:NoneConditions to Avoid: NoneHazardous Decomposition Products:

# SECTION 11 TOXICOLOGICAL INFORMATION

N/A

N/A

N/A

Eye	Effects:	

Skin Effects:

**Toxicity Data:\*** 

Acute Inhalation Effects:	N/A
Acute Oral Effects:	N/A
Chronic Effects:	N/A
Carcinogenicity:	N/A
Mutagenicity: Ames Test	(Estimated from the results of
Negative	testing the constituent components)
Teratogenicity:	N/A

\*See NIOSH, RTECS for additional toxicity data.

Ecotoxicity: N/A	
Environmental Fate: N/A	
Environmental Degradation:	N/A
Soil Absorption / Mobility:	N/A

Not specifically listed.

#### SECTION 13 DISPOSAL CONSIDERATIONS

**Disposal:** Waste material may be incinerated / or recycled for its Iron Oxide under conditions which meet all federal, state, and local environmental regulations.

Disposal Regulartory Requirements: N/A

Container Cleaning and Disposal: N/A

#### SECTION 14 TRANSPORT INFORMATION

N/A

N/A

N/A

N/A

N/A

N/A

DOT Transportation Data (49 CFR 172.101):

Shipping Name:

Hazard Class:

Packing Group:

Special Provisions: N/A

ID No:

Label:

Shipping Symbol:

Packaging Authorizationsa) Exceptions:N/Ab) Non-bulk Packaging:N/Ac) Bulk Packaging:N/A

Quantity Limitationsa) Passenger, Aircraft, orRailcar:N/A

Vessel Stowage Requirements a) Vessel Stowage: N/A b) Other: N/A

## SECTION 15 REGULATORY INFORMATION

# EPA Regulations:

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33) RCRA Hazardous Waste Classification: (40 CFR 261): Not classified CERCLA Hazardous Substance (40 CFR 302.4) listed unlisted specific per RCRA, sec. 3001; CWA sec.311 (b)(4); CWA, Sec. 307(a),CAA,Sec.112 CERCLA Reportable Quantity(RQ), Not listed SARA 311/312 Codes: N/A SARA Toxic Chemical (40 CFR 372.65): Not listed SARA Toxic Chemical (40 CFR 372.65): Not listed SARA EHS (Extremely Hazardous Substance) (40CFR 355): Not listed, Threshold Planning Quantity (TPQ)

### OSHA Regulations:

Air Containment (29 CFR 1910.1000< Table Z-1-A): Particulates not otherwise regulated.

**State Regulations:** Check your states regulations that may specifically list copy machine toner.

## SECTION 16 OTHER INFORMATION

Prepared By: N/A Revision Notes: N/A Additional Hazard Rating System: N/A

> THIS INFORMATION IN THIS MSDS WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY EXPRESS OR IMPLIED, REGARDLESS IT'S CORRECTNESS. THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE AND DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL, AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.