

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Identification of the

preparation

HP LaserJet Q2613A-X Print Cartridge

Use of the preparationThis product is a toner preparation that is used in HP LaserJet 1300 series printers.

Manufacturer information Hewlett-Packard Company 11311 Chinden Boulevard

Boise, ID 83714 USA

Hewlett-Packard health effects line

(Toll-free within the US) 1-800-457-4209 (Direct) 1-503-494-7199

General information telephone number

 HP Customer Care Line
 1-800-474-6836

 (Toll-free)
 1-800-474-6836

 (Direct)
 1-208-323-2551

 Date prepared
 Oct 11, 2005

MSDS number 82652

2. COMPOSITION / INFORMATION ON INGREDIENTS

Component/substance	CAS number	% by weight	
Styrene acrylate copolymer	Trade Secret	45 - 55	
Iron oxide	1317-61-9	40 - 50	

3. HAZARDS IDENTIFICATION

Acute health effects

Skin contact Unlikely to cause skin irritation.

Eye contact May cause transient slight irritation

Inhalation Minimal respiratory tract irritation may occur with exposure to large amounts of toner dust.Ingestion Low acute toxicity. Ingestion is a minor route of entry for intended use of this product.

Potential health effects

Routes of exposure Potential routes of exposure under normal use conditions are skin and eye contact; and

inhalation.

Ingestion is not expected to be a primary route of exposure for this product under normal use

conditions.

Chronic health effects Prolonged inhalation of excessive amounts of any dust may cause lung damage. Use of this

product as intended does not result in inhalation of excessive amounts of dust.

Carcinogenicity None of the ingredients have been classified as carcinogens according to EU, IARC, MAK,

NTP. OSHA or ACGIH.

Other information This product is not classified as hazardous according to OSHA CFR 1910.1200 or EU Directive

1999/45/EC, and as amended.

4. FIRST AID MEASURES

First aid procedures

Skin Wash affected areas thoroughly with mild soap and water. Get medical attention if irritation

develops or persists.

Eye Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for

at least 15 minutes or until particles are removed. If irritation persists, consult a physician.

Material nameQ2613A-XMSDS USCreation dateOct 28, 2004Version number 31 / 5



Inhalation Move person to fresh air immediately. If irritation persists, consult a physician.

Ingestion Rinse mouth out with water. Drink one to two glasses of water. If symptoms occur, consult a

physician.

5. FIRE FIGHTING MEASURES

Flash point and method Not applicable

Auto ignition temperature Not applicable

Hazardous combustion

products

Carbon monoxide and carbon dioxide.

Extinguishing media CO2, water, or dry chemical

Unsuitable extinguishing

media

None known.

Unusual fire and explosion

hazard

Like most organic material in powder form, toner can form explosive dust-air mixtures when

finely dispersed in air.

Fire fighting

equipment/instructions

If fire occurs in the printer, treat as an electrical fire.

Special firefighting procedures None established.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Minimize dust generation and accumulation. Avoid breathing dust.

Environmental precautions Do not flush into surface water or sanitary sewer system. See also section 13 Disposal

considerations.

Procedures if material is

released or spilled

Slowly vacuum or sweep the material into a bag or other sealed container. Clean remainder with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated as dust explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in compliance

with federal, state, and local regulations.

7. HANDLING AND STORAGE

Handling Keep out of the reach of children. Avoid inhalation of dust and contact with skin and eyes. Use

with adequate ventilation. Keep away from excessive heat, sparks, and open flames.

Storage Keep out of the reach of children. Store at room temperature in the original container. Keep the

container tightly closed and dry. Store away from strong oxidizers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit values USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)

ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)

TRGS 900 (Luftgrenzwert) - 10 mg/m3 (Einatembare partikel), 3 mg/m3 (Alveolengängige

fraktion)

Personal protective equipment

General No personal respiratory protective equipment required under normal conditions of use.

Exposure guidelines Use in a well ventilated area.

9. PHYSICAL & CHEMICAL PROPERTIES

pH Not applicableVapor pressure Not applicableBoiling point Not applicable

Melting point 100 - 150 °C (212.0 - 302.0 °F) (Softening point)

Material nameQ2613A-XMSDS USCreation dateOct 28, 2004Version number 32 / 5



Softening point 100 - 150 °C (212.0 - 302.0 °F)

Solubility Negligible in water. Partially soluble in toluene and xylene.

Specific gravity 1.4 - 1.8 (H2O = 1)

Flash point

Viscosity

Not applicable

Vapor density

Not applicable

Evaporation rate

Flammability

Not flammable

Appearance

Fine powder

Form solid

Odor Slight plastic odor

Oxidizing properties No information available.

Other information Decomposition temperature: > 200 degrees C

Color Black

10. CHEMICAL STABILITY & REACTIVITY INFORMATION

Stability Stable under normal storage conditions.

Conditions to avoid Imaging Drum: Exposure to light

Hazardous polymerization Will not occur.

Hazardous decomposition

products

Carbon monoxide and carbon dioxide.

Incompatibility Strong oxidizers

11. TOXICOLOGICAL INFORMATION

Complete toxicity data are not available for this specific formulation

Refer to Section 3 for potential health effects and Section 4 for first aid measures.

Dermal irritation Not classified as irritant, according to OSHA Hazard Communication Standard (HCS) and EU

Directive 67/548/EEC and as amended.

Eye irritation Not classified as irritant, according to OSHA Hazard Communication Standard (HCS) and EU

Directive 67/548/EEC and as amended.

Sensitization Not classified as a sensitizer according to EU Directive 67/548/EEC and as amended, and

OSHA HCS (US).

Chronic toxicity No information available.

 $\label{eq:continuous} \textbf{Oral toxicity} \hspace{1.5cm} \text{LD50/oral/rat} > 2000 \text{ mg/kg} \hspace{0.2cm} \text{, Not harmful. (OECD 401)}$

Inhalation toxicity LC50: inh/rat > 5 mg/l/4 hrs., not harmful (OECD 403).

Not classified for acute inhalation toxicity according to EU Directive 67/548/EEC and

1999/45/EC.

Carcinogenicity Not a known or suspected carcinogen according to any IARC Monograph, NTP, OSHA

Regulations (USA), EU Directive, or Proposition 65 (California).

Mutagenicity Negative, does not indicate mutagenic potential (Ames Test: Salmonella typhimurium)

Reproductive toxicity Not classified as toxic according to EU Directive 67/548/EEC and as amended, California Prop.

65, and DFG (Germany).

Material name Q2613A-X

Creation date Oct 28, 2004

Version number 3

MSDS US

Version number 3



12. ECOLOGICAL INFORMATION

Other information This product has not been tested for ecological effects.

13. DISPOSAL CONSIDERATIONS

Disposal instructionsDo not shred print cartridge, unless dust-explosion prevention measures are taken. Finely

dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal,

state, and local regulations.

HP's Planet Partners (trademark) supplies recycling program enables simple, convenient

recycling of HP original inkjet and LaserJet supplies. For more information and to determine if

this service is available in your location, please visit http://www.hp.com/recycle.

14. TRANSPORTATION INFORMATION

General Not a regulated article under United States DOT, IATA, ADR, IMDG, or RID.

IATA

Proper shipping name Not applicable

Special precautions None
Packaging exceptions None
Identification number (UN) None
Packing group N/A

15. REGULATORY INFORMATION

under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South

Korea, New Zealand, and China.

US Federal regulations US EPA TSCA Inventory: All chemical substances in this product comply with all rules or

orders under TSCA.

US TSCA 12(b): Contains p-Xylene (CAS No. 106-42-3), subject to export notification

requirements.

State regulations This product contains no chemical substances subject to rules or orders under California

Proposition 65.

HMIS ratings Health: 1 Flammability: 1

Flammability: 1 Physical hazard: 0

NFPA ratings Health: 1 Flammability: 1

Flammability: 1 Instability: 0

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely hazardous substance

No

Section 311 hazardous

chemical

No

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

Material name Q2613A-X

Creation date Oct 28, 2004

Version number 3

MSDS US

4 / 5



16. OTHER INFORMATION

This MSDS was prepared in accordance with USA OSHA Hazard Communications regulation Other information

(29 CFR 1910.1200).

Issue date Oct 11 2005 2:27PM

Revision

Jun 16 2005 10:46AM Replaces sheet dated

Disclaimer This Safety Data Sheet document is provided without charge to customers of Hewlett-Packard

Company. Data is the most current known to Hewlett-Packard Company at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in

Section 1 above and may not meet regulatory requirements in other countries.

1. Chemical Product and Company Identification: Identification of the preparation MSDS sections updated

1. Chemical Product and Company Identification: Use of the preparation

3. Hazards Identification: Routes of exposure

8. Exposure Controls/Personal Protection: Exposure limit values

11. Toxicological Information: Inhalation toxicity

Explanation of abbreviations

American Conference of Governmental Industrial Hygienists **ACGIH**

CAS Chemical Abstracts Service

CERCLA Comprehensive Environmental Response Compensation and Liability Act

Code of Federal Regulations **CFR**

COC Cleveland Open Cup

DOT Department of Transportation

EPCRA Emergency Planning and Community Right-to-Know Act (aka SARA)

IARC International Agency for Research on Cancer

NIOSH National Institute for Occupational Safety and Health

National Toxicology Program **NTP**

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

RCRA Resource Conservation and Recovery Act

REC Recommended

REL Recommended Exposure Limit

SARA Superfund Amendments and Reauthorization Act of 1986

STEL Short-Term Exposure Limit

Toxicity Characteristics Leaching Procedure **TCLP**

TLV Threshold Limit Value

TSCA Toxic Substances Control Act VOC Volatile Organic Compounds

Material name Q2613A-X MSDS US Creation date Oct 28, 2004 Version number 3

5/5