

21450/21461
21670/21675

Hygieia Chalk

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072



Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

IDENTITY (As Used on Label and List)
All CP/AP Products

None. Blank spaces are not permitted. If any item is not applicable, or no
information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name Dixon Ticonderoga Co.	Emergency Telephone Number (419) 625-9545
Address (Number, Street, City, State, and ZIP Code) 1706 Hayes Avenue Sandusky, OH 44870	Telephone Number for Information (419) 625-9545
	Date Prepared 6/16/92
	Signature of Preparer (optional) Thomas E. Swinard

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specify Chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (approx)
Products bearing the CP certified products or AP approved products seals of the Art and Craft Materials Institute, Inc. are certified in a program of toxicological evaluation by a medical expert, subject to review by the institute's toxicological advisory board to contain no materials in sufficient quantities to be toxic or injurious to humans or cause acute or chronic health problems.				
Conforms to ASTM D4236				
Approximately 98% Calcium Carbonate.				

Section III - Physical/Chemical Characteristics

Boiling Point	NA	Specific Gravity (H ₂ O = 1)	NA
Vapor Pressure (mm Hg)	NA	Melting Point	NA
Vapor Density (AIR = 1)	NA	Evaporation Rate (Butyl Acetate = 1)	NA
Solubility in Water	NA		
Appearance and Odor	White chalk, 3 1/2" x 3/8" diameter, no odor		

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)	NA	Flammable Limits	NA	LEL	NA	UEL	NA
Extinguishing Media	Water spray, foam, CO ₂						
Special Fire Fighting Procedures	Containers may be subject to ignition by fire and may release toxic or other irritating gases.						
Unusual Fire and Explosion Hazards	A self contained breathing apparatus should be used for this exposure.						

21450-21461, 21670-21675

21450

SMA-NW

Pg. 2

00000000

002

Section V — Reactivity Data

Reactivity	Unstable		Conditions to Avoid	NONE
	Stable	X		

Incompatibility (Materials to Avoid) NONE

Hazardous Decomposition or Byproducts NONE

Hazardous Polymerization	May Occur		Conditions to Avoid	NONE
	Will Not Occur	X		

Section VI — Health Hazard Data

Route(s) of Entry: NA Inhalation? Skin? Ingestion?

Acute Hazard (Irritant and Chronic) NONE

Carcinogenicity: NONE NTP? IARC Monographs? OSHA Registered?

Signs and Symptoms of Exposure NA

Medical Conditions Generally Aggravated by Exposure NA

Emergency and First Aid Procedures NA

Section VII — Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled

Sweep up or wash to suitable

waste disposal area.

Waste Disposal Method

Disposal should be made in accordance with Federal, State and Local regulations.

Precautions to be Taken in Handling and Storing

Do not store near heat or open flame

Other Precautions None.

Section VIII — Control Measures

Respiratory Protection (Specify Type) NA

Ventilation	Local Exhaust	NA	Special	NA
	Mechanical (General)	NA	Other	NA

Protective Gloves NA Eye Protection NA

Other Protective Clothing or Equipment NA

Work/Hygiene Practices NA