

401 Professional Drive Gaithersburg, MD 20879 Tel 301.590.9781

PAP 56201

Page 1 of 4

MATERIAL SAFETY DATA SHEET

NAME: LIQUID PAPER MULTI FLUID CORRECTION FLUID (LPCF-19-13)

CAS NO: NA

Effective Date: 12/10/98

Rev: 2

A. — IDENTIFICATION							
Composition*		%	Formula:		Mixture		
Titanium Dioxide (13463-67-7)			Molecular We	aight:	NA		
Solvent Naphtha (64742-89-8)			Synonyms:	<u>.</u>	<u></u> .		
Mineral Spirits (64742-48-9)					Multi Fluid		
Resin, Dispersant, Colorant(s)							
Mustard Oil (57-06-7)			1				
Fragrance	ſ						
B. — PHYSICAL DATA			<u> </u>				
Boiling Point	<u> </u>	Maltin	g Point		E		
209-230 °F 98-110 °C	NA	°F	NA	°c	NA °F	ng Point NA	°c
Specific Gravity (H ₂ O=1)			······································	. <u> </u>	Vapor Pressure @		
1.21	1	Vapor Density (air=1)			-		- °F
		3.3			124	mm Hg	;
Evaporation (Butyl Acetate =1)	(by volume	Saturation in Air (by volume@ °F)			Autoignition °F	Temperature	°-
3.6		'/)		T.A.	°C
% Volatiles			NA NA			A	
~43	Solubility in Water Negligible		pН	NT A			
						NA	
Appearance/Odor White fluid with	a pungent so	lvent	odor			_	
Flash Point and Test Method(s) 25.5°F (Closed C	Cup) for produ	uct					
Flammable Limits in Air							
(% by volume)	Lower		1%		Upper 5	8%	
C. — REACTIVITY							
Stability 🔀 stable	unstable	е	Polymeriza	ation	may occur	W will not	t occur
Conditions to Avoid					Conditions to Avoid		
Product is flammable. Avoid contact or other ignition sources.	t with open f	lame	NA				
Incompatible Materials				Hazan	dous Decomposition Pr	oducte	
Strong oxidizers			Thermal degradation may produce oxides of carbon				
-			and nitrogen and various hydrocarbons.				
						ود و و و و و و و و	
* IF MULTIPLE INGREDIENTS, IN(Footnotes	LUDE CAS	NUM	BERS FOR	EACH	NA=NO	T AVAILABI	1 2
Physical data, except Specific Gravit	v and % Vol	atiles	refere to Sal	vont 7	Jonhtha a commission		
predominantly C7 and C8 hydrocarb	.y anu 70 v 012 Ons	annes,	101015 10 301	vent 1	vapitina, a complex	i mixture or	
	~						

<u></u>	Page 2 of 4
	TH HAZARD DATA
	xposure Limits PEL's, TLV's, etc.)
8-Hour TWA	's: Rubber Solvent (Naphtha) - 400 ppm (OSHA/ACGIH) recommended.
	Titanium Dioxide - 10 mg/cu m (OSHA/ACGIH)
	Mineral Spirits – 300 ppm (Manufacturer recommendation)
These levels	are not anticipated under foreseeable use conditions.
Warning Signal	S
NA	
Routes/Effects	of Exposure
1. Inhalation	No adverse effects anticipated from normal use. If vapors are deliberately concentrated and inhaled (abuse), the following symptoms may occur: respiratory irritation, dizziness, drowsiness, headache, nausea, unconsciousness, convulsions, cardiac sensitization, coma and death. (Mustard oil added to the product as an abuse deterrent.)
2. Ingestion	No adverse effects anticipated from normal use. Depending on amount ingested, most of the symptoms described above may occur. Estimated LD_{50} in rats is greater than 5 ml/kg or between 1 pint and 1 quart in humans (ref. Gosselin, Smith and Hodge, Clinical Toxicology o Commercial Products, 5th Ed., 1984). Aspiration may result in chemical pneumonitis.
3. Skin	a. <u>Contact</u> No adverse effects anticipated from normal use. Irritation may occur if contact is prolonged/repeated.
	b. <u>Absorption</u> No adverse effects anticipated from normal use. Solvent can be absorbed through skin (prolonged contact), but not likely in acutely toxic amounts.
4. Eye Contact	If splashed into eye, irritation can occur.
5. Other	NA
E. — ENVIF	RONMENTAL IMPACT gulations
2. DOT Hazard C 8. DOT Shipping	OKW-D
nvironmental E	
	ts of this product comply with the U.S. Toxic Substances Control Act (TSCA).
	GMEL# 1303

)

``

F. — EXPOSURE CONTROL METHODS

Engineering Controls

None under normal use conditions.

Eye Protection None under normal use conditions.

Skin Protection None under normal use conditions.

Respiratory Protection None under normal use conditions.

Other

Product is non-hazardous when used as directed in an office/room with normal air circulation.



G. -- WORK PRACTICES

Handling and Storage

Product is flammable. No unusual handling or storage requirements. Storage in large quantities (as in warehouse) should be in a well-ventilated, cool area, away from ignition sources.

Normal Clean Up Pick up spills with towels, tissues, etc.

Waste Disposal Methods Dispose in accordance with applicable federal, state and local laws.

H. — EMERGENCY PROCEDURES

Steps to be taken if material is released to the environment or spilled in the work area Not applicable

Fire and Explosion Hazard	Extinguishing Media
Product is flammable. May produce hazardous decomposition	tion products. Dry chemical, foam, carbon
	dioxide.

Firefighting Procedures

In fires involving large quantities of product, use self-contained breathing apparatus. Cool fire-exposed containers with water fog/spray.

I. — FIRST AID AND MEDICAL EMERGENCY PROCEDURES

Eyes

Flush eyes with plenty of water. If irritation persists, obtain medical attention.

Skin

Wash with soap and water.

Inhalation

No adverse effects anticipated from normal use. In an abuse situation, remove from source of exposure. Treat symptomatically. Oxygen may be administered. Seek medical attention immediately and refer to "Notes to Physician" below.

Ingestion

Consult physician.

Notes to Physician

Contains solvent naphtha and mineral spirits which, if aspirated, may cause chemical pneumonitis. The inhalation of concentrated vapors may produce cardiac sensitization, contraindicating the use of sympathomimetic agents.

Replaces #1260, Sections A, D revised.

The information contained in the Material Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.