#96061

MATERIAL SAFETY DATA SHEET

Manufacturer:	MSDS Preparer: U.S. Testing Co., Inc.	Date: March 30, 1994 Supersedes: Feb. 1, 1994				
Wite-Out Products, Inc. 145 Southchase Blvd. Fountain Inn, SC 29644	Hoboken, NJ 07030* *Specific Technical information provided	Page 1 of 3 Emergency Telephone No.: (800) 424-9300 (CHEMTREC) Information Telephone No.: (203) 783-2103				
I. <u>PRODUCT INFORMATION</u> Identity: Wite-Out [®] For Everything [®] Correction Fluids (Quick Dry, Extra Coverage, Super Smooth) and MULTI PURPOSE Commercial Pack. Chemical Name: N/A Chemical Family: N/A Formula: For Everything [®] #114-054, #104-45, #114-011, #104-45C CAS Registry Number: N/A DOT Shipping Name: Consumer Commodity (As packaged for retail sale) DOT Hazard Class: ORM-D (As packaged for retail sale)						

II. HAZARDOUS INGREDIENTS

<u>Component(s)</u>	00	Hazard Information			
Petroleum Naphtha	40	OSHA PEL	ACGIH TLV	<u>OTHERS</u>	
(CAS #64742-48-9)		400ppm	400ppm	Flammable	

III. PHYSICAL AND CHEMICAL CHARACTERISTICS

Boiling Point, °F: 224-228 Vapor Pressure (mm Hg): 30-77 at 70°F Vapor Density (Air = 1): volatile components, 3.4 (Estimated) Solubility in Water: Practically Insoluble (0.5-0.8g/l) Appearance and Odor: Free flowing liquid with petroleum solvent odor Specific Gravity, (H2O=1): Correction fluid 1.25 Melting Point: 28°F Evaporation Rate (Butyl Acetate=1): volatile components, 1.1-1.5

IV. FIRE AND EXPLOSION HAZARD DATA

Flammable Liquid: Can release vapors that form flammable mixture at or above flash point. Flash Point (Method Used): 19-33°F (ASTM D3828-87)

Flammability Limits in Air, LEL: 1.2-1.9 UEL: 10.5-12.0

Extinguishing Media for Fires: CO₂, Foam, Dry Chemical Special Fire Fighting Procedures: Flammable liquid. Wear selfcontained breathing apparatus. Unusual Fire and Explosion Hazards: Toxic combustion gas may be formed as decomposition products.

N/A - Not Available

HONG MAREARS AREADS

<u>Formula</u>: Wite-Out[®] For Everything[®] Correction Fluids (Quick Dry, Extra Coverage, Super Smooth) and MULTI PURPOSE Commercial Pack Page 2 of 3 Date: March 30, 1994

96061

V. REACTIVITY DATA

Stability: [] Unstable [X] Stable Conditions to Avoid: Heat source, sparks or flame Materials to Avoid: Strong oxidizing or reducing agents Hazardous Decomposition Products: Toxic fumes or gases Hazardous Polymerization Products: []May Occur [X]May Not Occur Conditions to Avoid: Heat source, spark or flame

VI. HEALTH HAZARD DATA - Please See Section II

Carcinogen or	Potential	Carcinogen	<u>NTP:</u>	IARC:	<u>OSHA:</u>
			N/A	N/A	N/A
Health Hazard	(Acute or	Chronic):			

Skin: Not a primary skin irritant per the FHSA. May induce skin irritation in sensitive individuals. Eyes: Extra Coverage - Not an eye irritant per the FHSA; Quick Dry and Super Smooth - Eye irritant per the FHSA.

Ingestion: LD50 = >15 g/kg (Rat) Human Ingestion Hazard: Not known

Inhalation: Not hazardous under normal use conditions. Effects of Over Exposure: Effect - central nervous system depression; Likely route-Inhalation. Deliberately concentrating and inhaling content can lead to unconsciousness and/or death. Medical Conditions Generally Aggravated By Exposure: Existing pulmonary or dermal condition.

EMERGENCY AND FIRST AID PROCEDURES

Skin: Wash with soap and water. Consult physician if irritation occurs and persists.

Eyes: Wash with water. Consult physician if irritation occurs Ingestion: Consult physician at once. Do not induce vomiting. Inhalation: Remove victim from exposure. Alert emergency medical personnel. Administer artificial respiration if breathing is stopped.

VII. PRECAUTIONS FOR SAFE HANDLING AND USE

....

Spill or Leak Procedures: Handle as flammable liquid and dispose of properly. Ventilate area.

Disposal Recommendations: In accordance with state or federal guidelines.

Storage and Handling Recommendations: Store and transport in closed container. Store in ventilated area. Avoid heat, fire and fumes. Other Precautions: Keep away from children.

Wite-Out[®] For Everything[®] Correction Fluids (Quick Dry, Extra Formula: Coverage, Super Smooth) and MULTI PURPOSE Commercial PackPage 3 of 3

96061

Date: March 30, 1994

593

VIII. CONTROL MEASURES

Respiratory Protection: Respirator with organic vapor cartridge when handling bulk. None necessary under normal use conditions. Ventilation: []Local [X]Mechanical []Special []Other Protective Gloves: Chemical resistant gloves when handling bulk. None necessary under normal use conditions. Eye Protection: Use OSHA-approved goggles when handling bulk. None necessary under normal use conditions. Other Protective Equipment or Clothing: None required. Work Hygiene Practice: Standard good industrial hygiene practice recommended.

IX. REGULATORY INFORMATION

California Proposition 65: This product complies with the labeling requirement of the California Safe Drinking Water and Toxic Enforcement Act of 1986. OTHERS: This product does not contain chemicals known to deplete the ozone layer.

Wite-Out Products, Inc. believes that the information contained herein (including data and statements) is accurate as of the date hereof. NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE AS CONCERNS THE INFORMATION HEREIN PROVIDED. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use of the product and the information referred to herein are beyond the control of Wite-Out Products, Inc. (references to Wite-Out Products, Inc. including its divisions, parents, affiliates, and subsidiaries), Wite-Out Products, expressly disclaims any and all liability as to any results Inc. obtained or arising from any use of the product or such information. No statement made herein shall be construed as a permission or recommendation for the use of any product in a manner that might infringe existing patents.