

Aug 22 06 03:45p

Saral Paper Corp

(212)223-8111

p.3

**12917-4012****M A T E R I A L   S A F E T Y   D A T A   S H E E T****TRANSFER YELLOW**

Page: 1

**PRODUCT NAME:** TRANSFER YELLOW  
**PRODUCT CODE:** 72687**HMIS CODES:** H F R P  
2 3 0 G**===== SECTION I - MANUFACTURER IDENTIFICATION =====****MANUFACTURER'S NAME:** GOTHAM INK COMPANY  
**ADDRESS:** 19 KAY FRIES DRIVE  
STONY POINT, NY 10980  
INTERNATIONAL EMERGENCY#011-813-979-0626  
**CHEMTEL EMERGENCY:** 1-800-255-3924 **DATE PRINTED:** 08/21/06  
**INFORMATION PHONE:** 1-845-947-4000 **NAME OF PREPARER:** JOSEPH CLOHCSEY**===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====**

| REPORTABLE COMPONENTS                                          | CAS NUMBER | VAPOR PRESSURE<br>mm Hg @ TEMP | WEIGHT<br>PERCENT |
|----------------------------------------------------------------|------------|--------------------------------|-------------------|
| N-PROPANOL<br>OSHA TLV: 200 PPM, ACQSH TWA: 200 PPM, OTHER: NA | 71-23-8    | 13.00000 55.00000              | 32                |
| ETHYL ALCOHOL<br>OSHA: 1000 PPM TWA, ACQSH: 1000 PPM TWA       | 64-17-5    | 40.0 60.0                      | 5                 |

\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*  
SHIPPING CLASSIFICATION: FLAMMABLE LIQ. 3.2, UN 1210

**===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====****BOILING RANGE:** N/A **SPECIFIC GRAVITY (H2O=1):** 1.23  
**VAPOR DENSITY:** HEAVIER THAN AIR **EVAPORATION RATE:** < N-BUTYL ACETATE  
**COATING V.O.C.:** 4.86 lb/gal **MATERIAL V.O.C.:** 4.52 lb/gal  
**SOLUBILITY IN WATER:** Not soluble  
**APPEARANCE AND ODOR:** Colored liquid / typical solvent odor  
\* Varnish, Topcoat & Extender have Clear to Amber or Offwhite appearance.**===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====****FLASH POINT:** <100 deg F **METHOD USED:** TCC  
**FLAMMABLE LIMITS IN AIR BY VOLUME-** LOWER: 2.10000 **UPPER:** 21.2  
**EXTINGUISHING MEDIA:** FOAM, CO2, DRY CHEMICAL, WATER FOG**SPECIAL FIREFIGHTING PROCEDURES**

Self-contained breathing apparatus with full face piece operated in pressure demand or other positive pressure mode. During emergency conditions over exposure to decomposition products may cause immediate or delayed health hazards.

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

Vapors are heavier than air and may travel along the ground and be ignited by heat, open flame or other ignition sources. Keep containers tightly closed. Isolate from heat, sparks, electrical equipment, and open flames. Closed containers may polymerize and explode when exposed to extreme heat.

**===== SECTION V - REACTIVITY DATA =====****STABILITY:** STABLE  
**CONDITIONS TO AVOID**

Do not expose to high temperatures or open ignition sources.

Aug 22 06 03:44p

Saral Paper Corp

(212)223-8111

p.2

**M A T E R I A L   S A F E T Y   D A T A   S H E E T**  
**TRANSFER YELLOW**

Page: 2

**INCOMPATIBILITY (MATERIALS TO AVOID)**

Avoid contact with strong oxidizing agents.

**HAZARDOUS DECOMPOSITION OR BYPRODUCTS**

May form toxic materials, carbon dioxide, carbon monoxide, various hydrocarbons, etc on thermal decomposition.

**HAZARDOUS POLYMERIZATION: WILL NOT OCCUR****===== SECTION VI - HEALTH HAZARD DATA =====**  
N/A**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Excessive inhalation of vapors can cause nasal and respiratory irritation, weakness, dizziness, fatigue, nausea, headache and possible unconsciousness. Very severe exposure may cause respiratory depression and possible convulsions.

**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Prolonged or repeated skin contact can cause moderate irritation, dermatitis. May cause pain and severe eye irritation such as excess tearing, redness and blurred vision.

**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Organic solvents are easily absorbed; drying of the skin, redness or dermatitis are signs of repeated or overexposure to the solvent's defatting action.

**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Can cause moderate gastrointestinal irritation, nausea, vomiting &amp; diarrhea, indigestion and general weakness. May cause kidney &amp; liver damage.

**HEALTH HAZARDS (ACUTE AND CHRONIC)**

ACUTE-EYES: Can cause severe irritation, redness, tearing, and blurred vision. SKIN: Can cause severe irritation, defatting and dermatitis. INHALATION: Can cause nasal and respiratory irritation. Aspiration into lungs can cause chemical pneumonitis which can be fatal. CHRONIC: Very prolonged or repeated exposure above TLV may result in permanent brain &amp; nervous system damage.

**CARCINOGENICITY:** NTP CARCINOGEN: No **IARC MONOGRAPHS:** No **OSHA REGULATED:** No  
None known at this time.**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE**

Prolonged or exposure to very high concentrations of vapors may aggravate existing dermatitis or produce blood disorders.

**EMERGENCY AND FIRST AID PROCEDURES**

EYES: Flush immediately with large amounts of water for at least 15 minutes. Take to a physician for medical treatment. SKIN: Wash affected areas with soap and water. Remove contaminated clothing. Consult a physician if irritation persists. INHALATION: Remove to fresh air. Restore breathing. Treat symptomatically. Consult a physician. INGESTION: Drink 1 or 2 glasses of water to dilute. Do not induce vomiting. Consult a physician or poison control center immediately. Treat symptomatically.

**===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====****STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Eliminate all ignition sources. Dike, contain, or absorb with inert materials (sand, vermiculite, etc.). Transfer to containers for recovery or disposal. Prevent runoff into sewers, streams, or other bodies of water. GROUND WORK EQUIPMENT.

**WASTE DISPOSAL METHOD**

Dispose of in accordance with all local, state, or federal regulations.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

Do not store or use near sources of high temperatures, heat fire or open flame, or other ignition sources. Keep container clean. NOTE: ALL CONTAINERS MUST BE GROUNDED AND BONDED WHEN POURING.

Aug 26 06 03:44p

Saral Paper Corp

(212)223-8111

p.1

**M A T E R I A L   S A F E T Y   D A T A   S H E E T**  
**TRANSFER YELLOW****Page: 3****OTHER PRECAUTIONS**

Do not take internally. Avoid prolonged or repeated exposure to levels above TLV. Hot organic chemical vapors or mists are susceptible to sudden spontaneous combustion when mixed with air. Ignition may occur at typical elevated-temperature process conditions. Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained.

**===== SECTION VIII - CONTROL MEASURES =====****RESPIRATORY PROTECTION**

If TLV is exceeded use NIOSH/MSHA approved organic vapor and mist, supplied air or self contained breathing apparatus.

**VENTILATION**

Use adequate mechanical (general and/or local) ventilation to maintain exposure below TLV. Special local ventilation is recommended at points where vapors can be expected to escape to the workplace air.

**PROTECTIVE GLOVES**

Wear resistant gloves such as nitrile rubber.

**EYE PROTECTION**

Use chemical splash goggles or other OSHA permitted safety glasses.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

Wear impervious clothing. Eyewash stations.

**WORK/HYGIENIC PRACTICES**

Wash hands before eating or using restrooms. Remove and wash contaminated clothing before reuse.

**===== SECTION IX - DISCLAIMER =====**

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees.