MATERIAL SAFETY DATA SHEET

Product Name: Product Number (s	Ice-Off® Windshield Spray De):05346, 75346	e-icer			
Manufactured By:	CRC Industries, Inc. 885 Louis Drive, Warminster, P.	(215) 674-4300 (800) 424-9300			
	24-Hour Emergency Information				
Section 2: Composit	ion/Information on Ingredients				
Component	CAS NUMBER	ACGIH TLV	OSHA PEL	OTHER LIMITS	%
Methanol	67-56-1	200 ppm	200 ppm	200 ppm	> 90
Propylene glycol	57-55-6	NE	NE	50 ppm	< 10
Water Carbon Dioxide	7732-18-5 124-38-9	NE 5000 ppm	NE 5000 ppm	NE 5000 ppm	< 10 < 10
	Emergence	v Overview			
	U	cy overview			
	C C	2	liquid		
	Appearance & Odor: (2	e liquid.		
Danger: Flammabl	C C	Clear, water-white	-	Contents Under	Pressur
	Appearance & Odor: (e. Vapor Harmful. May be fatal or	Clear, water-white	-	Contents Under	Pressur
Potential Health Eff	Appearance & Odor: (e. Vapor Harmful. May be fatal of ects:	Clear, water-white r cause blindness	-	Contents Under	Pressur
Danger: Flammabl Potential Health Eff Inhalation: Eyes:	Appearance & Odor: (e. Vapor Harmful. May be fatal or	Clear, water-white r cause blindness	-	Contents Under	Pressur
Potential Health Eff Inhalation: Eyes: Skin:	Appearance & Odor: (e. Vapor Harmful. May be fatal or ects: Drowsiness, nausea and vomitin Irritation Burning, itching and redness.	Clear, water-white r cause blindness g.	if swallowed. C	Contents Under	Pressur
Potential Health Eff Inhalation: Eyes:	Appearance & Odor: (e. Vapor Harmful. May be fatal or ects: Drowsiness, nausea and vomitin Irritation	Clear, water-white r cause blindness g.	if swallowed. C	Contents Under	Pressur
Potential Health Eff Inhalation: Eyes: Skin:	Appearance & Odor: C e. Vapor Harmful. May be fatal or ects: Drowsiness, nausea and vomitin Irritation Burning, itching and redness. Inebriation, headache, nausea, bl	Clear, water-white r cause blindness g.	if swallowed. C		Pressur
Potential Health Eff Inhalation: Eyes: Skin: Ingestion: Carcinogenicity: Chronic Overexposu	Appearance & Odor: (e. Vapor Harmful. May be fatal or ects: Drowsiness, nausea and vomitin Irritation Burning, itching and redness. Inebriation, headache, nausea, bl OSHA: No IA re: NA	Clear, water-white <u>r cause blindness</u> g. lindness and death .RC: No A	if swallowed. C		Pressur
Potential Health Eff Inhalation: Eyes: Skin: Ingestion: Carcinogenicity: Chronic Overexposu	Appearance & Odor: C e. Vapor Harmful. May be fatal or ects: Drowsiness, nausea and vomitin Irritation Burning, itching and redness. Inebriation, headache, nausea, bl OSHA: No IA re: NA Aggravated by Exposure: NA	Clear, water-white <u>r cause blindness</u> g. lindness and death JRC: No A A	if swallowed. C	: No	
Potential Health Eff Inhalation: Eyes: Skin: Ingestion: Carcinogenicity: Chronic Overexposu	Appearance & Odor: (e. Vapor Harmful. May be fatal or ects: Drowsiness, nausea and vomitin Irritation Burning, itching and redness. Inebriation, headache, nausea, bl OSHA: No IA re: NA Aggravated by Exposure: NA	Clear, water-white <u>r cause blindness</u> g. lindness and death JRC: No A A	if swallowed. C	: No	
Potential Health Eff Inhalation: Eyes: Skin: Ingestion: Carcinogenicity: Chronic Overexposu Medical Conditions	Appearance & Odor: (e. Vapor Harmful. May be fatal or ects: Drowsiness, nausea and vomitin Irritation Burning, itching and redness. Inebriation, headache, nausea, bl OSHA: No IA re: NA Aggravated by Exposure: NA	Clear, water-white <u>r cause blindness</u> g. lindness and death .RC: No A A	if swallowed. C	: No	
Potential Health Eff Inhalation: Eyes: Skin: Ingestion: Carcinogenicity: Chronic Overexpost Medical Conditions Section 4: First Aid	Appearance & Odor: (e. Vapor Harmful. May be fatal or ects: Drowsiness, nausea and vomitin Irritation Burning, itching and redness. Inebriation, headache, nausea, bl OSHA: No IA re: NA Aggravated by Exposure: NA	Clear, water-white r cause blindness g. lindness and death IRC: No A A Cial respiration if	if swallowed. C	: No	
Potential Health Eff Inhalation: Eyes: Skin: Ingestion: Carcinogenicity: Chronic Overexpost Medical Conditions Section 4: First Aid	Appearance & Odor: (e. Vapor Harmful. May be fatal or ects: Drowsiness, nausea and vomitin Irritation Burning, itching and redness. Inebriation, headache, nausea, bl OSHA: No IA re: NA Aggravated by Exposure: NA Measures Remove to fresh air. Give artific	Clear, water-white r cause blindness g. lindness and death RC: No A A cial respiration if er for 15 minutes.	if swallowed. C	: No	

Product Name: Ice-Off® Windshield Spray De-icer

Section 5: Fire-Fighting Measures

Flashpoint:	55 °]	F	Method:	ГСС	LEL: 6.0		UEL: 36.5
Extinguishir	ng Media:		Carbon dioxide	, dry chemical	and foam.		
Hazardous Combustion Products:		Thermal - Carbon monoxide, CO ₂					
Fire-fighting	g Instructions:		Remove contain	ners from fire a	area if possible. Use	self-co	ontained
			breathing appar above 120°F.	atus for fire fig	ghting. Aerosol cans	s may e	explode if heated
NFPA:	Health:	2	Flammability:	3	Reactivity:	0	
HMIS:	Health:	2	Flammability:	3	Reactivity:	0	PPE: B

Section 6: Accidental Release Measures

Spill/Leak Procedures: Usually not a problem with aerosols. Area should be ventilated. Absorbent should be used to pick up excess material. All used and unused product should be disposed of in accordance with federal, state and local regulations.

Section 7: Handling and Storage

Storage Procedures: Store in a cool, dry area. Aerosol cans must be maintained below 120°F to prevent cans from exploding.

Section 8: Exposure Controls/Personal Protection

Engineering Controls: Adequate to prevent accumulation of vapors. Use mechanical means if necessary to maintain levels below the exposure limits. If working in a confined space, follow applicable OSHA regulations.

Respiratory: Use NIOSH/MSHA compliant respirators or self-contained breathing apparatus above exposure limits. Follow OSHA regulations 29 CFR 1910.134.

Protective Clothing/Equipment: Wear chemically protective gloves and safety glasses. Use a splash apron and boots if splashing occurs.

Section 9: Physical & Chemical Properties

Physical State: Specific Gravity:	Liquid 0.8031	Appearance & Odor: Boiling Point:	Clear, water-white liquid. 147 °F
Freezing Point:	ND	Vapor Pressure:	96 mm
Evaporation Rate:	Fast	Vapor Density (air $= 1$)	1.11
pH:	NA	Solubility:	Complete with water.
Volatile Organic Compo	unds:%: 89.0	g/L: 729	lbs./gal: 6.08

Section 10: Stability and Reactivity

Stability:	Stable	Hazardous Polymerization:	No
Chemical Incompatibilities:	Strong oxidizers.		
Materials to Avoid:	Sources of ignition.		
Hazardous Decomposition Products:	None		

Page 3 of 3

Product Name: Ice-Off® V Section 11: Toxicological In	Product Number (s): 05346, 75346		
C	dies have not been cond osure and carcinogenici	ty information.	uct. See Section 3 of this MSDS for
Section 12: Ecological Infor			
Ecotoxicity: Environmental Fate:		-	
Section 13: Disposal Consid			
activities must comply with agency for specific rules. D	federal, state and local o not dump into sewers	regulations. Conta s, on the ground or	
Section 14: Transportation I			
Shipping Name: Hazard Class: Label: Special Provisions:	Consumer Commodi ORM-D NA NA	UN Number: NA Placard: NA	A
Section 15: Regulatory Info			
TSCA: SARA Title III: CERCLA/Superfund (RQ): Extremely Hazardous Substa California Prop 65:	All components are e Section 311/312: ances:	either listed under T Acute, Pressure Mixture No No	SCA or are exempt. Section 313*: Methanol
* See section 2 for percentag	ge		
Section 16: Additional Infor	mation		
Prepared By: Technical Information: This information is accurate CRC to be accurate. Before		-	November 7, 2003 638 or obtained from sources believed by directions on the label.
CAS: Chemical Abstr ppm: Parts per Millio TCC: Tag Closed Cup LEL: Lower Explosiv UEL: Upper Explosiv PPE: Personal Protect COC: Cleveland Close	n e Limit e Limit tion Equipment	NA: ND: NE: g/L: lbs./gal: RQ: TOC:	Not Applicable Not Determined Not Established grams per Liter pounds per gallon Reportable Quantity Tag Open Cup