

Product Name: WITE-OUT® Brand Shake 'n Squeeze Correction Pen

MATERIAL SAFETY DATA SHEET

Date Prepared: January 18, 2010 Version 4

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION		
Product Name:	WITE-OUT® Brand Shake 'n Squeeze Correction Pen WITE-OUT® Brand Mini Shake 'n Squeeze Correction Pen	
Synonyms:	WP1 Fluid (Correction Fluid)	
Product Use:	Correction fluid	
Manufacturer/ Vendor Information:	Manufactured for/Distributed by: BIC Corporation One BIC Way, Suite 1 Shelton, CT 06484 USA (203) 783-2000 Emergency Telephone Number: (203) 783-2412 Supplier Information: BIC Inc. 155 Oakdale Road Downsview, Ontario M3N 1W2 CANADA (416) 742-9173 x288 (Business hours)	
MSDS Contact:	Product Safety	
Telephone number:	(203) 783-2124	

Substance or	Preparation:		
CAS No.	Chemical Name	ACGIH (TLV) and OSHA (PEL) Exposure Limits	% by Weight
13463-67-7	Titanium dioxide	TLV-TWA: 10 mg/m ³ PEL- TWA: 15 mg/m ³	30-60
64741-66-8	Naphtha (petroleum), light alkylate	Not applicable	15-40
64742-49-0	Naphtha petroleum, hydrotreated light	TLV-TWA: 400 ppm TLV-STEL: 500 ppm PEL- TWA: 500 ppm (Recommended based on a similar substance – Heptane)	15-40

TLV = Threshold Limit Value, PEL = Permissible Exposure Limit, TWA= Time-Weighted Average

SECTION 3 - HAZARDS IDENTIFICATION		
Most Important Hazards:	HIGHLY FLAMMABLE LIQUID	
	Deliberately concentrating and inhaling this product can lead to Central Nervous	
	System (CNS) effects, unconsciousness and/or death. Aspiration hazard if	
	swallowed. Product may be irritating if inhaled accidentally.	
For more information refer to Section 11 of this MSDS		

	SECTION 4 - FIRST-AID MEASURES
Eyes:	Quickly and gently blot or brush away chemical. Flush contaminated eye(s) with lukewarm, gently flowing water for 5 minutes or until the chemical is removed. If irritation occurs, obtain medical advice.
Skin:	If irritation does occur, flush with lukewarm gently flowing water for 5 minutes or until chemical is removed. As quickly as possible, remove contaminated clothing, shoes, and leather goods (e.g. watchbands, belts) as the product is highly flammable.
Inhalation:	If breathing has stopped, trained personnel should begin artificial respiration (AR) or, if the heart has stopped, cardiopulmonary resuscitation (CPR) immediately. Immediately transport victim to an emergency care facility.
Ingestion:	DO NOT INDUCE VOMITING. Aspiration hazard if swallowed. Have victim drink 240-300 mL (8-10 oz) of water to dilute material in stomach. NEVER give anything by mouth to someone who is unconscious or rapidly losing consciousness. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration and repeat administration of water. Quickly transport victim to an emergency care facility.

SECTION 5: FIRE-FIGHTING MEASURES		
Flash point:	-5°C (23°F) (Seta Flash Closed Cup)	
Conditions of flammability:	HIGHLY FLAMMABLE. Can release vapors that form flammable mixtures at or above the flash point.	
	1.7% by volume 12.3 % by volume	
Extinguishing Media:	CO ₂ , Foam, Dry Chemical	
Special Firefighting Procedures:	Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.	
Hazardous Combustion Products:	Carbon monoxide, carbon dioxide, reactive hydrocarbons, carbonyl compounds, smoke and irritating vapours may be formed on combustion.	

SECTION 6: ACCIDENTAL RELEASE MEASURES		
	Highly flammable liquid. Wear appropriate personal protective equipment for your use. Ventilate area. In case of large spills, wear self-contained breathing apparatus.	
	Avoid contaminating sewers, streams, rivers and other watercourses with spilled material. Absorb with inert absorbent material (do not use flammable materials like cloth or paper) and dispose of properly.	

SECTION 7: HANDLING AND STORAGE	
Handling	
Handling:	Highly flammable liquid. Wear appropriate personal protective equipment for your use. Avoid contact with skin and eyes. Wash thoroughly after handling this product. Avoid contact with heat and sources of ignition.
U U	Store in a cool, dry, well-ventilated area. Store away from incompatible and reactive materials (See Sections 5 and 10). Keep container tightly closed. Store away from heat and sources of ignition.

Correction Pen, WP-1 Fluid

SECTION 8: EXPOSURE CONTROLS/ PERSONAL PROTECTION

The selection of personal protective equipment varies, depending upon the conditions of use. Use equipment appropriate to your particular use pattern.

Engineering Measures:	For normal application, special ventilation is not necessary. If handling in bulk use mechanical explosion-proof ventilation.	
Eye Protection:	Not required except when handling bulk. If handling in bulk wear chemical safety goggles.	
Hand Protection:	None necessary under normal conditions. Chemical resistant gloves when handling bulk.	
Skin and Body Protection:	Wear appropriate clothing to avoid prolonged or repeated skin contact.	
Respiratory Protection:	None necessary under normal use conditions. Respirator with organic vapour cartridge when handling in bulk.	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES		
Appearance & Physical State:	Free flowing liquid.	
Melting Point:	Not available.	
Boiling Point:	95.6-113.9°C (204-237°F)	
Decomposition Temperature:	Not Available	
Auto-ignition Temperature:	~246.1°C (based on Petroleum Solvent - approximate)	
Explosion Properties- Sensitivity to Mechanical		
Impact:	Not Available	
Sensitivity to Static		
Discharge:	Not Available	
Density/Specific Gravity:	1.25 (Water =1)	
Odour/Odour Threshold:	Petroleum solvent odour/ Not available	
Evaporation Rate:	0.89-1.08 (Butyl Acetate=1)	
pH:	Not Available	
Octanol/ Water Partition Coefficient	Not Available	
Vapour Pressure:	26-49 mmHg at 20°C	
Vapour Density:	3.4-4.0 (estimated) (air =1)	
Solubility in Water:	0.1 g/L at 20°C	

SECTION 10: STABILITY AND REACTIVITY		
Stability:	Stable	
Conditions to avoid:	Avoid heat sources, sparks or flames and static discharge.	
Materials to avoid:	Avoid strong oxidizing or reducing agents, strong acids and strong bases.	
	Toxic fumes or gases such as carbon monoxide, carbon dioxide and reactive hydrocarbons. Specific decomposition products are not available.	
Hazardous Polymerization:	Not expected to undergo hazardous polymerization.	

S	ECTION 11: TOXI	COLOGICAL INFORMA	TION
Routes of Entry:	Skin contact, Inhala	ation, Eye contact, Skin Ab	sorption, Ingestion
Acute Toxicity			
Product data:			
Route & Species	<u>Value</u>		
Oral; rat, LD ₅₀	>15 g/kg		
Inhalation; rat LC_{50}	90-169.4 mg/L/1H		
	0		
Ingredient data:			
<u>Chemical</u>	CAS#	Route & Species	<u>Value</u>
Methylcyclohexane	108-87-2	Dermal; rabbit, LD ₅₀	>86 700 mg/kg
Titanium dioxide	13463-67-7	Dermal; rabbit, LD ₅₀	>10 000 mg/kg
Naphtha (petroleum), light	64741-66-8	Dermal; rabbit, LD ₅₀	>2000 mg/kg
alkylate	04741 00 0		22000 mg/kg
Naphtha petroleum,	C4740 40 0	Dermel rehbit I D	2100
hydrotreated light	64742-49-0	Dermal; rabbit, LD ₅₀	>3160 mg/kg
Eye Irritation:	Not expected to be	an eve irritant based on th	e results of an <i>in vitro</i> ocular
Eye Irritation: Not expected to be an eye irritant based on the results of an <i>in vitro</i> tolerance test.			
Skin Irritation:			d on the results of a human skin
	patch test and an i		
Skin Sensitization:			use skin sensitization, based
Respiratory Tract		data and the known hazard roduct is not expected to ca	
Sensitization:			nd the known hazards of the
	components.		
Chronic Toxicity			
Carcinogenicity:			nts, the product is not expected t
	pose a carcinogeni	,	
Mutagenicity:	This product is not known to contain any components at $>= 0.1\%$ that have been shown to cause mutagenicity. Therefore, based upon the available data		
	and the known hazards of the components, this product is not expected to be a		
	mutagen.	· · ·	· ·
Reproductive Toxicity:	This product is not known to contain any components at $>= 0.1\%$ that have		
	been shown to cause reproductive toxicity. Therefore, based upon the		
	available data and the known hazards of the components, this product is not expected to be a reproductive toxin.		
Teratogenicity/Embryotoxicity			
	been shown to cause teratogenicity and/or embryotoxicity. Therefore, based		
		data and the known hazard	
		ected to be a teratogen/emb	
Other Chronic Effects:	Repeated and chronic product abuse such as deliberately concentrating and inhaling this product can result in adverse effects to the CNS such as		
	drowsiness, dizziness and potentially serious long-term health effects.		
Toxicologically Synergistic			

SECTION 12: ECOLOGICAL INFORMATION		
Mobility:	Not Available	
Persistence/ Degradability:	Not Available	
Bioaccumulation:	Not Available	
Ecotoxicity:	Not Available	

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal Method: In accordance with local, provincial/territorial or federal guidelines and regulations

	SECTION 14 - TRANSPORT INFORM	ATION		
	Shipping name	UN Number	Hazard Class	PG
DOT (US)	For domestic transport by road, rail and cargo: Proper Shipping Name: Consumer Commodity Class: ORM-D			
	For domestic transport by air Proper Shipping Name: Consumer Commodity Class: ORM-D-AIR			
	For International transport by cargo vessel, road, rail: Proper shipping name: Coating Solution	1139	3	II
	For international transport by Air: Proper Shipping Name: Consumer Commodity	ID8000	9	
TDG (Canada):	COATING SOLUTION	1139	3	II

WHMIS Sy	mbols for Labelling Purpo	DSES:	
Ľ			
	•	zard Communication Standard (29 C	CFR §1910.1200))
OSHA Cla Flammable	•	zard Communication Standard (29 C	CFR §1910.1200))
	•	zard Communication Standard (29 C	CFR §1910.1200))
Flammable	rd Ratings:	·	
Flammable Other Haza	rd Ratings: NPCA/HMI	·	704
Flammable	rd Ratings: NPCA/HMI	·	

SECTION 16 - OTHER INFORMATION

Disclaimer: The information given is based on data currently available to us and is believed to be correct. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. No responsibility is assumed for injury or damage from the use of the products described herein.